


**Single Remote Pilot, 3-way, 2-position, Xtreme Operating Pressure / Temperature**



P2LAX Shown

Port size (NPT)	Cv	Response time (msec)	Weight lb (kg)	Valve type	Part number
1/8"	0.7	15 / 45	0.68 (0.31)	P2LAX	<b>P2LAX391PS</b>
1/4"	1.3	25 / 65	0.68 (0.31)	P2LBX	<b>P2LBX392PS</b>
3/8"	2.5	25 / 65	0.88 (0.40)	P2LCX	<b>P2LCX393PS</b>
1/2"	2.7	25 / 65	0.88 (0.40)	P2LDX	<b>P2LDX394PS</b>


**Single Remote Pilot, 4-way, 2-position, Xtreme Operating Pressure / Temperature**



P2LAX Shown

Port size (NPT)	Cv	Response time (msec)	Weight lb (kg)	Valve type	Part number
1/8"	0.7	15 / 45	0.33 (0.15)	P2LAX	<b>P2LAX591PS</b>
1/4"	1.3	20 / 55	0.68 (0.31)	P2LBX	<b>P2LBX592PS</b>
3/8"	2.5	25 / 85	0.90 (0.41)	P2LCX	<b>P2LCX593PS</b>
1/2"	2.7	25 / 85	0.90 (0.41)	P2LDX	<b>P2LDX594PS</b>

**Double Remote Pilot, 4-way, 2-position, Xtreme Operating Pressure / Temperature**



P2LBX Shown

Port size (NPT)	Cv	Response time (msec)	Weight lb (kg)	Valve type	Part number
1/8"	0.7	11 / 11	0.33 (0.15)	P2LAX	<b>P2LAX591PP</b>
1/4"	1.3	13 / 13	0.68 (0.31)	P2LBX	<b>P2LBX592PP</b>
3/8"	2.5	18 / 18	0.90 (0.41)	P2LCX	<b>P2LCX593PP</b>
1/2"	2.7	18 / 18	0.90 (0.41)	P2LDX	<b>P2LDX594PP</b>

**Double Remote Pilot, 4-way, 3-position All Ports Blocked, 3-position Center Exhaust, Xtreme Operating Pressure / Temperature**



P2LBX Shown

Port size (NPT)	Cv	Response time (msec)	Weight lb (kg)	Valve type	Part number	
					All ports blocked	Center exhaust
1/8"	0.5	18 / 50	0.31 (0.14)	P2LAX	<b>P2LAX691PP</b>	<b>P2LAX891PP</b>
1/4"	0.9	25 / 65	0.73 (0.33)	P2LBX	<b>P2LBX692PP</b>	<b>P2LBX892PP</b>
3/8"	1.8	30 / 90	0.93 (0.42)	P2LCX	<b>P2LCX693PP</b>	<b>P2LCX893PP</b>
1/2"	1.9	30 / 90	0.93 (0.42)	P2LDX	<b>P2LDX694PP</b>	<b>P2LDX894PP</b>

**Notes:** Above valves are rated for an operating temperature from -40°F to 140°F (-40°C to 60°C). See model code matrix for additional options.  
 Response time: Actuate to 90% pressure / return to exhaust to 10% of supply pressure. 93 PSIG (6.3 bar) / temperature 68°F (20°C).

**Remote Air Pilot Operated Valves**

**P2L A X 5 91 PS**

Valve size	
1/8"	<b>A</b>
1/4"	<b>B</b>
3/8"	<b>C*</b>
1/2"	<b>D*</b>

\* P2LCX and P2LDX manual & remote air pilot valves have a maximum pressure rating of 175 PSIG (12 bar).

Operators / return	
<b>PP</b>	Double remote pilot
<b>PS*</b>	Single remote pilot, spring return

\* Not available with 3-position valves.

Main port thread	
11	G1/8 (P2LA)
12	G1/4 (P2LB)
13	G3/8 (P2LC)
14	G1/2 (P2LD)
<b>91</b>	<b>1/8" NPT (P2LA)</b>
<b>92</b>	<b>1/4" NPT (P2LB)</b>
<b>93</b>	<b>3/8" NPT (P2LC)</b>
<b>94</b>	<b>1/2" NPT (P2LD)</b>

Note: NAMUR Mount for P2LBX is available upon request.

Valve type / function	
<i>Internal pilot supply to solenoid</i>	
3/2 NC - 2-position	<b>3</b>
5/2 2-position	<b>5</b>
5/3 3-position, APB	<b>6</b>
5/3 3-position, PC	<b>7</b>
5/3 3-position, CE	<b>8</b>

Most popular.



Viking Lite Series

Viking Xtreme Series

B Series

ADEX Series

N Series

**D**

Inline Valve Products